

## PRODUCT DATA SHEET

### MPI-S700

**Brand Name:** MicroPoly MPI-S700  
**Manufacturer:** PhyMet, Inc.  
**Shelf Life:** Many years at < 90°F  
**Structure:** Oil Filled Porous Polymer  
**Fluid:** Synthetic PAO and Additives

Oil Viscosity	CST	SUS
@40°C/100°F:	149	788
@100°C/210°F:	19.0	94

**Viscosity Index of Oil:** 144  
**Temperature:** Max: 250°F  
Min: - 49°F  
**Color:** Green  
**Oil Specific Gravity:** 0.86  
**Additives:** Anti Rust, Anti Oxidant, EP Additive  
**Water Resistance:** Good  
**Copper Corrosion:** 1B (24 hours @ 121°C)

This information is for reference only.  
This document contains confidential and proprietary trade secret information. It is the property of PhyMet, Inc. and is given to the receiver in confidence. The receiver by reception and retention of the document accepts the document in confidence and agrees that, except as authorized in writing by PhyMet, Inc. it will (1) not disclose the document or any copy thereof or the confidential or trade secret information therein, (2) not copy the document, (3) not disclose to others either the document or the confidential or trade secret information therein, and (4) upon completion of the need to retain the document, or upon demand, return the document, all copies thereof, and all material copied there from